


# BPM - 586 (LOW TORQUE)

## Profiling Machine for Bangle and Ring.

This is a table top machine to profile bangles and rings in any shape accurately. It has additional facility to operate manually. Precision depth setting device to control gauge, profile and diameter of Bangles and Rings.



- Only single roller set is required to profile bangles from ø1.5" to ø3 (ø38 to ø76 mm).
- Special bangle/ring profiling rollers set provided on customer's request.
- Special device and roller to maintain bangle and ring level.
- Ideal for small and medium size jewelry



- 1 Vertical Aperture Micromatic Steering
- 2 Vertical Aperture Micromatic Stopper Screw




- 1 Handle for Manual Operation
- 2 Main Switch




- 1 Bangle & Ring Width Leveling Device



- 1 APM02-31-02 : Bangle Profiling Roller (Top)
- 2 APM02-31-01 : Bangle Profiling Roller (Bottom)



- 1 APM01-33-02 : Bangle Flattening Roller (Top)
- 2 APM01-33-01 : Bangle Flattening Roller (Bottom)



- 1 APM03-33 : Ring Profiling Roller Bush
- 2 APM03-31-02 : Ring Profiling Roller (Top)
- 3 APM03-31-01 : Ring Profiling Roller (Bottom)

## Technical Specification

BPM - 586

Sr. No.	Technical Data	BPM - 586
01	Operating System	Manual/Motorized
02	Maximum Profile Thickness	20 Gauge
03	Maximum Width Of Bangles	3/4" (20 mm)
04	Bangle Profiling Diameter	1.1/2" To 3" (38 mm To 76 mm)
05	Maximum Width Of Ring	3/8" (10 mm )
06	Ring Profiling Diameter	1/2" To 1.15/32" (13 mm To 37 mm)
07	Roller Speed	40 rpm
08	Shaft Motor Single Phase	0.25 hp (0.18 kw) 220V AC
09	Total Required Electrical Load	0.75 kva
10	Dimension (L X W X H)	42 X 38 X 38 cms
11	Floor Space Required (L X W)	23 X 21 cms
12	Net Weight With Standard Accessories	55 kg
13	Gross Weight With Standard Accessories	102 kg
14	Shipping Dimension With Standard Accessories (L X W X H)	52 X 55 X 59 cms